

Pressure Control

PC-1 (Male & Female:Z1/4")



- 1.Lowest Pressure:20PSI
- 2.Highest Pressure:80psi
- 3.Pressure Setting:20-40PSI, 30-50PSI, 40-60PSI

PC-2 (Male&Female:Z1/4")



- 1.Pressure Range:0.7-3bar
- 2.Max.Current:5A
- 3.Msle&Femmale:Z1/4", Z3/8"
- 4.Rated Voltage:110V-220V
- 5.Max.Pressure:3bar
- 6.Pressur Settings:1.0-1.7bar 1.1-1.8bar

PC-3



- 1.Female:Z1/4"
- 2.Lowest Pressure:150PSI
- 3.Highest Pressure:175PSI
- 4.Environmental rating:Type1
- 5.Pressure Rating:40-70PSI, 50-80PSI, 70-100PSI, 80-115PSI, 90-125PSI, 105-145PSI, 135-175PSI to choose

PC-4



- 1.Min.Pressure(on):20PSI
- 2.Max.Pressure(off):175PSI
- 3.Joint Thread:Z1/4"
- 4.Pressure Settings:20-40PSI, 30-50PSI, 40-60PSI, 50-80PSI, 70-100PSI, 95-125PSI, 115-150PSI, 140-175PSI

PC-5



- 1.Joint Screw:Z1/4"
- 2.Pressure Range:20-175PSI
- 3.With one-way valve or with four-way valve
- 4.Pressure Settings:20--40PIS, 30-50PSI, 40-60PSI, 50-80PSI, 70-100PSI, 95-125PSI, 115-150PSI, 140-175PSI

PC-6



- 1.Joint Screw:Z1/4"
- 2.Lowest Pressure: 15PS
- 3.Highest Pressure: 175PSI
- 4.With one-way valve or With Four-way Valve
- 5.Environmental Rating: Type1
- 6.Pressure Rating: 40-70PSI, 50-80PSI, 70-100PSI, 80-115PSI, 90-125PSI, 105-145PSI, 135-175PSI to choose

PC-7



- 1.Rated Voltage:250V
- 2.Rated Current:16A(10A)
- 3.Joint Screw:ZG1/4"
- 4.Pressure Range:15-80PSI
- 5.Pressure Setting:20-40PSI
- 6.Proection Type:I
- 9.Active Type:1A
- 10.Single-phase or three-phase to choose

PC-9



- 1.Rated Voltage:220V-240V 110V-115V
- 2.Max.Current:10A.
- 3.Frequency:50-60HZ
- 4.Max.Power:1.1KW
- 5.Joint Screw:1"
- 6.Protection Grade:IP65
- 7.Starting pressure to choose:1.5bar,2.2bar

PC-10



- Descriptions:
- 1.Rated Voltage:220V or 110V-115V
 - 2.Max.current:10A
 - 3.Frequency:50-60HZ
 - 4.Max.Power:1.1KW
 - 5.Joint Screw:1"
 - 6.Protection Grade :IP65
 - 7.Starting Pressure to choose:1.5bar or 2.2 bar

PC-11



- Descriptions:
- 1.Rated Voltage:220V-240V or 110V-115V
 - 2.Max.current:10A
 - 3.Frequency:50-60HZ
 - 4.Max.Power:1.1KW
 - 5.Joint Screw:1"
 - 6.Protection Grade :IP65
 - 7.Starting Pressure to choose:1.5bar or 2.2bar

PC-12



- Descriptions:
- 1.Rated Voltage:220V-240V or 110V-115V
 - 2.Max.current:10A
 - 3.Frequency:50-60HZ
 - 4.Max.Power:1.1KW
 - 5.Joint Screw:1"
 - 6.Protection Grade :IP65
 - 7.Starting Pressure to choose:1.5bar or 2.2bar

PC-13



- Descriptions:
- 1.Rated Voltage:220V-240V or 110V-115V
 - 2.Max.current:10A
 - 3.Frequency:50-60HZ
 - 4.Max.Power:1.1KW
 - 5.Joint Screw:1"
 - 6.Protection Grade :IP65
 - 7.Starting Pressure to choose:1.5bar or 3 bar

PC-13A



- Descriptions:
- 1.Rated Voltage:220V-240V or 110V-115V
 - 2.Max.current:10A
 - 3.Frequency:50-60HZ
 - 4.Max.Power:1.1KW
 - 5.Joint Screw:1"
 - 6.Protection Grade :IP65
 - 7.Starting Pressure to choose:1.5bar or 3 bar

PC-15



- 1.Female:Z3/8"
- 2.lowest pressue:0.6Mpa
- 3.Highest Pressure:1.25Mpa
- 4.Max.Current:20A
- 5.Rated Voltage:110V-220V-380V

PC-20