

NT Series H.R.C Fuse Link & Base

NT type low voltage H.R.C. fuse features light in weight, small in size, low in power, loss and high in beaking capacity. This product has been widely used in overload and short circuit protection of electric installations.

This product conforms to IEC269 and VDE0636 standards of the rating at the world advanced level.

Specification

Type	Rated current (A)	Fuse link		Weight (kg)	Type	Fuse base	
		Rated voltage (V)	Rated power loss(W)			Rated current (A)	Weight (kg)
NT00C NT00	2	500,600	0.41	0.15	sist 101	160	0.2
	4		0.81				
	6		0.62				
	10		1.08				
	16		1.60				
	20		1.81				
	25		2.31				
	32		3.07				
	36		3.17				
	40		4.05				
	50		4.25				
	63		5.7				
	80		7				
100	1.03						
NT0	6	500,600	4.70	0.2	sist 101	160	0.32
	10	500,600	1.42				
	16	500,600	2.45				
	20	500,600	2.36				
	35	500,600	2.7				
	32	500,600	3.74				
	35	500,600	4.3				
	40	500,600	4.7				
	50	500,600	5.5				
	63	500,600	6.9				
	80	500,600	7.6				
	100	500,600	8.9				
	125	500	10.1				
160	500	15.2					

Type	Fuse link				Fuse base		
	Rated current (A)	Rated voltage (V)	Weight (kg)	Rated power loss(A)	Type	Rated current (A)	Weight (kg)
NT1	80	500 600	6.2	0.36	Sist201	250	0.8
	100	500 600	7.5				
	125	500 600	10.2				
	160	500 600	13				
	200	500 600	15.2				
	224	500	16.8				
	250	500	18.3				