

DS Current Transformers



DSM-20B



DSM-20



DSM-30



DS-30



DS-40



DS-60



DS-100

Technical data & Specification

Model	Rated Current (A) Primary/Secondary	Busbar Hole Dimension	Rated Burden (VA)	Accuracy Class	Rated Voltage	Rated Frequency
DSM-20B	50/5A-200/5A		1.5-3	1.0	660V	50/60Hz
DSM-20	50/5A-200/5A	20×10mm	1.5-3	1.0	660V	50/60Hz
DSM-30	50/5A-200/5A	20×10mm	1.5-3	1.0	660V	50/60Hz
DS-30	50/5A-300/5A	30×10mm	2.5-5	1.0	660V	50/60Hz
DS-40	150/5A-800/5A	40×10mm	5-10	1.0	660V	50/60Hz
DS-60	400/5A-1000/5A	60×10mm	10	1.0	660V	50/60Hz
DS-100	800/5A-3000/5A	100×10mm	15	1.0	660V	50/60Hz

Dimension of case (mm)

Model	A	B	C	D
DS-20A	56	30	63	80
DS-20	56	30	63	50
DS-30	56	30	63	50
DS-30	79	42	87	66
DS-40	79	42	87	66
DS-60	103	42	113	66
DS-100	151	42	166	69

Outline drawing

